

THE TALLMAX

FRAMED 144 LAYOUT MODULE



144 LAYOUT
MULTICRYSTALLINE MODULE

340-355W
POWER OUTPUT RANGE

17.7%
MAXIMUM EFFICIENCY

0~+5W
BINNING TOLERANCE

PRODUCTS
TSM-PE15H

POWER RANGE
340-355W

Founded in 1997, Trina Solar is the world's leading total solution provider for solar energy. With local presence around the globe, Trina Solar is able to provide exceptional service to each customer in each market and deliver our innovative, reliable products with the backing of Trina as a strong, bankable brand. Trina Solar now distributes its PV products to over 100 countries all over the world. We are committed to building strategic, mutually beneficial collaborations with installers, developers, distributors and other partners in driving smart energy together.

Comprehensive Products and System Certificates

IEC61215/IEC61730/IEC61701/IEC62716/UL61730

ISO 9001: Quality Management System

ISO 14001: Environmental Management System

ISO14064: Greenhouse Gases Emissions Verification

ISO45001: Occupation Health and Safety Management System



High power

- Up to 355W front power and 17.7% module efficiency with half-cut technology bringing more BOS savings
- Lower resistance of half-cut ensure high power



High reliability

- Ensured PID resistance through cell process and module material control
- Resistant to salt, acid and ammonia
- Mechanical performance: Up to 5400 Pa positive load and 2400 Pa negative load




High energy generation

- Excellent IAM and low light performance validated by 3rd party with cell process and module material optimization
- Better anti-shading performance and lower operating temperature


PERFORMANCE WARRANTY

12 Year Product Warranty · 25 Year Power Warranty




From the 2nd year to the 25th year, the average annual power decline will be no more than 0.65%.


DIMENSIONS OF PV MODULE(mm)



Front View




Back View




A-A

B-B

I-V CURVES OF PV MODULE(345W)



P-V CURVES OF PV MODULE(345W)



ELECTRICAL DATA (STC)

Peak Power Watts- P_{MAX} (Wp)*	340	345	350	355
Binning Tolerance- P_{MAX} (W)	0 ~ +5			
Maximum Power Voltage- V_{MPP} (V)	37.5	37.7	37.9	38.1
Maximum Power Current- I_{MPP} (A)	9.06	9.15	9.23	9.32
Open Circuit Voltage- V_{OC} (V)	46.2	46.4	46.7	47.0
Short Circuit Current- I_{SC} (A)	9.53	9.62	9.71	9.81
Module Efficiency η_m (%)	16.9	17.2	17.4	17.7

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5.
*Measuring tolerance: ±3%.

ELECTRICAL DATA (NOCT)

Maximum Power- P_{MAX} (Wp)	253	257	261	265
Maximum Power Voltage- V_{MPP} (V)	35.2	35.4	35.5	35.7
Maximum Power Current- I_{MPP} (A)	7.21	7.28	7.34	7.41
Open Circuit Voltage- V_{OC} (V)	43.2	43.3	43.6	43.9
Short Circuit Current- I_{SC} (A)	7.69	7.77	7.84	7.92

NOCT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

MECHANICAL DATA

Solar Cells	Multicrystalline
Cell Orientation	144 cells (6 × 24)
Module Dimensions	2015 × 996 × 35 mm (79.33×39.21×1.38 inches)
Weight	22.0 kg (48.5 lb)
Glass	3.2 mm (0.13 inches), High Transmission, AR Coated Heat Strengthened Glass
Encapsulant Material	EVA/POE
Backsheet	White
Frame	35 mm (1.38 inches) Anodized Aluminium Alloy
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm ² (0.006 inches ²), Portrait: N 280mm/P 280mm(11.02/11.02inches) Landscape: N 1400 mm /P 1400 mm (55.12/55.12 inches)
Connector	MC4 EVO2 / TS4

TEMPERATURE RATINGS

NOCT (Nominal Operating Cell Temperature)	43°C (±2°C)
Temperature Coefficient of P_{MAX}	- 0.38%/°C
Temperature Coefficient of V_{OC}	- 0.31%/°C
Temperature Coefficient of I_{SC}	0.05%/°C

(Do not connect Fuse in Combiner Box with two or more strings in parallel connection)

MAXIMUM RATINGS

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC (IEC) 1500V DC (UL)
Max Series Fuse Rating	20A

WARRANTY

- 12 year Product Workmanship Warranty
- 25 year Power Warranty

(Please refer to product warranty for details)

PACKAGING CONFIGURATION

- Modules per box: 31 pieces
- Modules per 40' container: 682 pieces