


THE

DUOMAX twin

BIFACIAL DUAL GLASS 144 HALF-CELL MODULE



144-Cell

MONOCRYSTALLINE MODULE

380-405W

POWER OUTPUT RANGE

20.0%

MAXIMUM EFFICIENCY

0~+5W

POSITIVE POWER TOLERANCE

PRODUCTS

TSM-DEG15HC.20(II)

POWER RANGE

380-405W



High power output

- Up to 405W front power and 20.0% module efficiency with half-cut technology enabling higher BOS savings
- Lower resistance of half-cut cells ensures higher power



Certified to perform in highly challenging environments

- High PID resistance through cell process and module material control
- Resistant to salt, acid, sand, and ammonia
- Proven to be reliable in high temperature and humidity areas
- Certified to the best fire class A
- Minimizes micro-crack and snail trails
- Certified to 5400 Pa positive load and 2400 Pa negative load



High energy generation, low LCOE

- Up to 25% additional power gain from back side, depending on the albedo
- Excellent 3rd party validated IAM and low light performance with cell process and module material optimization
- Low temp coefficient (-0.35%) and NMOT increases energy production
- Better anti-shading performance and lower operating temperature
- Higher power from same installation footprint as standard modules



Easy to install, wide application

- Frame design enables compatibility with standard installation methods
- Deployable for ground mounted utility, carports, and agricultural projects
- Safe and easy to transport, handle, and install like normal framed modules

Founded in 1997, Trina Solar is the world's leading total solution provider for solar energy. With local presence around the globe, Trina Solar is able to provide exceptional service to each customer in each market and deliver our innovative, reliable products with the backing of Trina as a strong, bankable brand. Trina Solar now distributes its PV products to over 100 countries all over the world. We are committed to building strategic, mutually beneficial collaborations with installers, developers, distributors and other partners in driving smart energy together.

Comprehensive Products and System Certificates

IEC61215/IEC61730/IEC61701/IEC62716

ISO 9001: Quality Management System


ISO 14001: Environmental Management System

ISO14064: Greenhouse Gases Emissions Verification

OHSAS 18001: Occupation Health and Safety Management System




Trina Solar's DUOMAX Performance Warranty



From the 2nd year to the 30th year, the average annual power decline will be no more than 0.5%.

DIMENSIONS OF PV MODULE (mm)



ELECTRICAL DATA (STC)

Peak Power Watts- P_{MAX} (Wp)*	380	385	390	395	400	405
Power Output Tolerance- P_{MAX} (W)	0 ~ +5					
Maximum Power Voltage- V_{MPP} (V)	40.3	40.4	40.5	40.6	40.7	40.8
Maximum Power Current- I_{MPP} (A)	9.43	9.53	9.63	9.73	9.83	9.93
Open Circuit Voltage- V_{OC} (V)	49.2	49.4	49.6	49.7	49.9	50.1
Short Circuit Current- I_{SC} (A)	9.99	10.09	10.19	10.29	10.39	10.49
Module Efficiency η_m (%)	18.7	19.0	19.2	19.5	19.7	20.0

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5.
*Measuring tolerance: ±3%.

ELECTRICAL DATA (NMOT)

Maximum Power- P_{MAX} (Wp)	289	292	296	300	304	308
Maximum Power Voltage- V_{MPP} (V)	38.1	38.2	38.3	38.4	38.6	38.7
Maximum Power Current- I_{MPP} (A)	7.58	7.65	7.73	7.81	7.88	7.95
Open Circuit Voltage- V_{OC} (V)	46.6	46.8	47.0	47.1	47.2	47.4
Short Circuit Current- I_{SC} (A)	8.05	8.13	8.21	8.29	8.37	8.45

NMOT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

Electrical characteristics with different rear side power gains (referenced specifically to 400 Wp front)**


Maximum Power- P_{MAX} (Wp)	420	440	460	480	500
Maximum Power Voltage- V_{MPP} (V)	40.7	40.7	40.7	40.7	40.7
Maximum Power Current- I_{MPP} (A)	10.32	10.81	11.30	11.80	12.29
Open Circuit Voltage- V_{OC} (V)	49.9	50.0	50.0	50.0	50.1
Short Circuit Current- I_{SC} (A)	10.91	11.43	11.95	12.47	12.99
P_{max} gain	5%	10%	15%	20%	25%

Power Bifaciality: 70±5%.


MECHANICAL DATA

Solar Cells	Monocrystalline
Cell Orientation	144 cells (6 × 24)
Module Dimensions	2024 × 1002 × 30 mm (79.69 × 39.45 × 1.18 inches)
Weight	26.0 kg (57.3 lb)
Front Glass	2.0 mm (0.08 inches), High Transmission, AR Coated Heat Strengthened Glass
Encapsulant material	POE/EVA
Back Glass	2.0 mm (0.08 inches), Heat Strengthened Glass (White Grid Glass)
Frame	30mm (1.18 inches) Anodized Aluminium Alloy
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0 mm ² (0.006 inches ²) Portrait: 280/280 mm (11.02/11.02 inches) Landscape: 1900/1900 mm (74.80/74.80 inches)
Connector	Trina TS4

I-V CURVES OF PV MODULE (400W)



P-V CURVES OF PV MODULE (400W)



TEMPERATURE RATINGS

NMOT (Nominal Module Operating Temperature)	41°C (±3°C)
Temperature Coefficient of P_{MAX}	- 0.35%/°C
Temperature Coefficient of V_{OC}	- 0.25%/°C
Temperature Coefficient of I_{SC}	0.04%/°C

(Do not connect Fuse in Combiner Box with two or more strings in parallel connection)

MAXIMUM RATINGS

Operational Temperature	-40 ~ +85°C
Maximum System Voltage	1500V DC (IEC) 1500V DC (UL)
Max Series Fuse Rating	20A

WARRANTY

12 year Product Workmanship Warranty
30 year Power Warranty
(Please refer to product warranty for details)

** Back-side power gain varies depending upon the specific project albedo

PACKAGING CONFIGURATION

Modules per box:	35 pieces
Modules per 40' container:	665 pieces
Pallet dimensions (L x W x H):	2060 x 1120 x 1178 mm
Pallet weight:	973kg (2,145lb)