



BACKSHEET MONOCRYSTALLINE MODULE

PRODUCT: TSM-XXXDE21

POWER RANGE: 645-670W

670W

MAXIMUM POWER OUTPUT

0~+5W

POWER SELECTION

21.6%

MAXIMUM EFFICIENCY



High customer value

- Lower LCOE (Levelized Cost Of Energy), reduced BOS (Balance of System) cost, shorter payback time
- Lowest guaranteed first year and annual degradation;
- Designed for compatibility with existing mainstream system components



High power Mono Perc up to 670W

- Up to 21.6% module efficiency with high density interconnect technology
- Multi-busbar technology for better light trapping effect, lower series resistance and improved current collection



High reliability


- Minimized micro-cracks with innovative non-destructive cutting technology
- Ensured PID resistance through cell process and module material control
- Resistant to harsh environments such as salt, ammonia, sand, high temperature and high humidity areas
- Mechanical performance up to 5400 Pa positive load and 2400 Pa negative load



High energy yield

- Excellent IAM (Incident Angle Modifier) and low irradiation performance, validated by 3rd party certifications
- The unique design provides optimized energy production under inter-row shading conditions
- Lower temperature coefficient (-0.34%) and operating temperature

Trina Solar's Backsheet Performance Warranty




Comprehensive Products and System Certificates




IEC61215/IEC61730/IEC61701/IEC62716
 ISO 9001: Quality Management System
 ISO 14001: Environmental Management System
 ISO14064: Greenhouse Gases Emissions Verification
 ISO45001: Occupational Health and Safety Management System




DIMENSIONS OF PV MODULE(mm)



I-V CURVES OF PV MODULE(650 W)



P-V CURVES OF PV MODULE(650W)



ELECTRICAL DATA (STC) TSM-XXXDE21(XXX=645-670)

Peak Power Watts -P _{MAX} (Wp)*	645	650	655	660	665	670
Power Selection -P _{MAX} (W)	0 ~ +5					
Maximum Power Voltage -V _{MPP} (V)	37.2	37.4	37.6	37.8	38.0	38.2
Maximum Power Current -I _{MPP} (A)	17.35	17.39	17.43	17.47	17.51	17.55
Open Circuit Voltage -V _{OC} (V)	45.1	45.3	45.5	45.7	45.9	46.1
Short Circuit Current -I _{SC} (A)	18.39	18.44	18.48	18.53	18.57	18.62
Module Efficiency η _m (%)	20.8	20.9	21.1	21.2	21.4	21.6

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5. *Measuring tolerance: ±3%.

ELECTRICAL DATA (NOCT)

Maximum Power -P _{MAX} (Wp)	488	492	496	500	504	508
Maximum Power Voltage -V _{MPP} (V)	34.8	34.9	35.1	35.3	35.4	35.6
Maximum Power Current -I _{MPP} (A)	14.05	14.09	14.13	14.17	14.22	14.26
Open Circuit Voltage -V _{OC} (V)	42.5	42.7	42.9	43.0	43.2	43.4
Short Circuit Current -I _{SC} (A)	14.82	14.86	14.89	14.93	14.96	15.01

NOCT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

MECHANICAL DATA

Solar Cells	Monocrystalline
No. of cells	132 cells
Module Dimensions	2384×1303×35 mm (93.86×51.30×1.38 inches)
Weight	33.6 kg (74.1 lb)
Glass	3.2 mm (0.13 inches), High Transmission, AR Coated Heat Strengthened Glass
Encapsulant material	EVA
Backsheet	White
Frame	35mm(1.38 inches) Anodized Aluminium Alloy
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm ² (0.006 inches ²), Portrait: 280/280 mm(11.02/11.02 inches) Length can be customized
Connector	MC4 EVO2 / Trina Solar TS4

TEMPERATURE RATINGS

NOCT (Nominal Operating Cell Temperature)	43°C (±2°C)
Temperature Coefficient of P _{MAX}	-0.34%/°C
Temperature Coefficient of V _{OC}	-0.25%/°C
Temperature Coefficient of I _{SC}	0.04%/°C

MAXIMUM RATINGS

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC (IEC) 1500V DC (UL)
Max Series Fuse Rating	30A

WARRANTY

12 year Product Workmanship Warranty
 25 year Power Warranty
 2% first year degradation
 0.55% Annual Power Attenuation

(Please refer to product warranty for details)

PACKAGING CONFIGURATION

Modules per box: 31 pieces
 Modules per 40' container: 558 pieces