

THE
Honey^M
 FRAMED 120 LAYOUT MODULE



120 LAYOUT
 MONOCRYSTALLINE MODULE

360-380W
 POWER OUTPUT RANGE

20.7%
 MAXIMUM EFFICIENCY

0~+5W
 BINNING TOLERANCE

PRODUCTS | POWER RANGE
 TSM-DD08M.08(II) | 360-380W

Founded in 1997, Trina Solar is the world's leading total solution provider for solar energy. With local presence around the globe, Trina Solar is able to provide exceptional service to each customer in each market and deliver our innovative, reliable products with the backing of Trina as a strong, bankable brand. Trina Solar now distributes its PV products to over 100 countries all over the world. We are committed to building strategic, mutually beneficial collaborations with installers, developers, distributors and other partners in driving smart energy together.

Comprehensive Products and System Certificates

IEC61215/IEC61730/IEC61701/IEC62716
 ISO 9001: Quality Management System
 ISO 14001: Environmental Management System
 ISO14064: Greenhouse Gases Emissions Verification
 ISO45001: Occupational Health and Safety Management System



High power Mono Perc

- Up to 380W front power and 20.7% module efficiency with half-cut and MBB (Multi Busbar) technology bringing more BOS savings
- Lower resistance of half-cut and good reflection effect of MBB ensure high power




High reliability

- Mechanical performance: Up to 5400 Pa positive load and 2400 Pa negative load and fire class rating C




High energy generation


- Excellent IAM and low light performance validated by 3rd party with cell process and module material optimization
- Lower temp coefficient (-0.34%) and NOCT bring more energy leading to lower LCOE
- Better anti-shading performance and lower operating temperature




DIMENSIONS OF PV MODULE(mm)




Front View




Back View



I-V CURVES OF PV MODULE(370W)



P-V CURVES OF PV MODULE(370W)



ELECTRICAL DATA (STC)

Peak Power Watts- P_{MAX} (Wp)*	360	365	370	375	380
Binning Tolerance- P_{MAX} (W)	0 ~ +5				
Maximum Power Voltage- V_{MPP} (V)	33.6	33.9	34.2	34.4	34.7
Maximum Power Current- I_{MPP} (A)	10.70	10.76	10.82	10.89	10.96
Open Circuit Voltage- V_{OC} (V)	40.7	41.0	41.3	41.6	41.9
Short Circuit Current- I_{SC} (A)	11.24	11.30	11.37	11.45	11.52
Module Efficiency η_m (%)	19.6	19.9	20.2	20.5	20.7

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5.
*Measuring tolerance: $\pm 3\%$.

ELECTRICAL DATA (NOCT)

Maximum Power- P_{MAX} (Wp)	271	275	279	282	286
Maximum Power Voltage- V_{MPP} (V)	31.5	31.8	32.0	32.2	32.5
Maximum Power Current- I_{MPP} (A)	8.60	8.65	8.71	8.77	8.83
Open Circuit Voltage- V_{OC} (V)	38.3	38.6	38.9	39.2	39.4
Short Circuit Current- I_{SC} (A)	9.06	9.10	9.16	9.23	9.28

NOCT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

MECHANICAL DATA

Solar Cells	Monocrystalline
Cell Orientation	120 cells (6 × 20)
Module Dimensions	1763 × 1040 × 35 mm (69.41 × 40.94 × 1.38 inches)
Weight	20.0 kg (44.1 lb)
Glass	3.2mm (0.13 inches), High Transmission, AR Coated Heat Strengthened Glass
Encapsulant Material	EVA
Backsheet	White
Frame	35 mm (1.38 inches) Anodized Aluminium Alloy
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm ² (0.006 inches ²), Portrait: N 280mm/P 280mm(11.02/11.02inches) Landscape: N 1200 mm /P 1200 mm (47.24/47.24 inches)
Connector	PV-KBT4(female),PV-KST4(male) /TS4

TEMPERATURE RATINGS

NOCT (Nominal Operating Cell Temperature)	43 C (± 2 C)
Temperature Coefficient of P_{MAX}	- 0.34%/ C
Temperature Coefficient of V_{OC}	- 0.25%/ C
Temperature Coefficient of I_{SC}	0.04%/ C

(Do not connect Fuse in Combiner Box with two or more strings in parallel connection)

WARRANTY

- 15 year Product Workmanship Warranty
- 25 year Power Warranty
- 2% first year degradation
- 0.55% Annual Power Attenuation

(Please refer to product warranty for details)

MAXIMUM RATINGS

Operational Temperature	-40 ~ +85 C
Maximum System Voltage	1000V DC (IEC)
Max Series Fuse Rating*	20A / 25A

*Default 20A / 25A upon special request

PACKAGING CONFIGURATION

- Modules per box: 30 pieces
- Modules per 40' container: 780 pieces