

THE
Honey^M
 FRAMED 120 LAYOUT MODULE



120 LAYOUT
 MONOCRYSTALLINE MODULE

355-375W
 POWER OUTPUT RANGE

20.5%
 MAXIMUM EFFICIENCY

0~+5W
 BINNING TOLERANCE

PRODUCTS	Frame Color	POWER RANGE
TSM-DE08M(II) TSM-DE08M.08(II)	Silver Black	355-375W

Founded in 1997, Trina Solar is the world's leading total solution provider for solar energy. With local presence around the globe, Trina Solar is able to provide exceptional service to each customer in each market and deliver our innovative, reliable products with the backing of Trina as a strong, bankable brand. Trina Solar now distributes its PV products to over 100 countries all over the world. We are committed to building strategic, mutually beneficial collaborations with installers, developers, distributors and other partners in driving smart energy together.

Comprehensive Products and System Certificates

IEC61215/IEC61730/IEC61701/IEC62716
 ISO 9001: Quality Management System
 ISO 14001: Environmental Management System
 ISO14064: Greenhouse Gases Emissions Verification
 OHSAS 18001: Occupation Health and Safety Management System



High power Mono Perc

- Up to 375W front power and 20.5% module efficiency with half-cut and MBB (Multi Busbar) technology bringing more BOS savings
- Lower resistance of half-cut and good reflection effect of MBB ensure high power



High reliability


- Resistant to salt, acid and ammonia and fire class rating C
- Certified to 5400 Pa positive load and 2400 Pa negative load




High energy generation

- Excellent IAM and low light performance validated by 3rd party with cell process and module material optimization
- Lower temp coefficient (-0.36%) and NMOT bring more energy leading to lower LCOE
- Better anti-shading performance and lower operating temperature


PERFORMANCE WARRANTY




DIMENSIONS OF PV MODULE(mm)




Front View




Back View



I-V CURVES OF PV MODULE(365W)



P-V CURVES OF PV MODULE(365W)



ELECTRICAL DATA (STC)

Peak Power Watts-P _{MAX} (Wp)*	355	360	365	370	375
Binning Tolerance (W)	0 ~ +5				
Maximum Power Voltage-V _{MPP} (V)	33.4	33.6	33.9	34.2	34.4
Maximum Power Current-I _{MPP} (A)	10.62	10.70	10.76	10.82	10.89
Open Circuit Voltage-V _{OC} (V)	40.4	40.7	41.0	41.3	41.6
Short Circuit Current-I _{SC} (A)	11.16	11.24	11.30	11.37	11.45
Module Efficiency η_m (%)	19.4	19.6	19.9	20.2	20.5

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5.
*Measuring tolerance: ±3%.

ELECTRICAL DATA (NMOT)

Maximum Power-P _{MAX} (Wp)	268	272	276	280	283
Maximum Power Voltage-V _{MPP} (V)	31.5	31.7	32.0	32.2	32.4
Maximum Power Current-I _{MPP} (A)	8.51	8.57	8.62	8.67	8.73
Open Circuit Voltage-V _{OC} (V)	38.1	38.4	38.7	39.0	39.3
Short Circuit Current-I _{SC} (A)	8.99	9.05	9.10	9.15	9.22

NMOT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

MECHANICAL DATA

Solar Cells	Monocrystalline
Cell Orientation	120 cells (6 × 20)
Module Dimensions	1763 × 1040 × 35 mm (69.41 × 40.94 × 1.38 inches)
Weight	20.0 kg (44.1 lb)
Glass	3.2mm (0.13 inches), High Transmission, AR Coated Heat Strengthened Glass
Encapsulant Material	EVA
Backsheet	White
Frame	35 mm (1.38 inches) Anodized Aluminium Alloy
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm ² (0.006 inches ²), Portrait: N 280mm/P 280mm(11.02/11.02inches) Landscape: N 1200 mm /P 1200 mm (47.24/47.24 inches)
Connector	Stabuli MC4 EVO2 / Trina Solar TS4

TEMPERATURE RATINGS

NMOT (Nominal Module Operating Temperature)	41 C (±3 C)
Temperature Coefficient of P _{MAX}	-0.36%/C
Temperature Coefficient of V _{OC}	-0.26%/C
Temperature Coefficient of I _{SC}	0.04%/C

MAXIMUM RATINGS

Operational Temperature	-40~+85 C
Maximum System Voltage	1500V DC (IEC) 1500V DC (UL)
Max Series Fuse Rating*	20A /25A

*Default 20A / 25A upon special request

WARRANTY

15 year Product Workmanship Warranty
25 year Power Warranty
2% first year degradation
0.55% Annual Power Attenuation

(Please refer to product warranty for details)

PACKAGING CONFIGURATION

Modules per box: 30 pieces
Modules per 40' container: 780 pieces