


Mono

Multi

Solutions

THE Quadmax MODULE



DC80.08

72 CELL
MONOCRYSTALLINE MODULE

210-215W
POWER OUTPUT RANGE

16.8%
MAXIMUM EFFICIENCY

0~+3%
POWER OUTPUT GUARANTEE

As a leading global manufacturer of next generation photovoltaic products, we believe close cooperation with our partners is critical to success. With local presence around the globe, Trina is able to provide exceptional service to each customer in each market and supplement our innovative, reliable products with the backing of Trina as a strong, bankable partner. We are committed to building strategic, mutually beneficial collaboration with installers, developers, distributors and other partners as the backbone of our shared success in driving Smart Energy Together.

Trina Solar Limited
www.trinasolar.com

Trinasolar
Smart Energy Together



Excellent power density with highest efficiency
• Up to 168W/m² power density



Great aesthetics for residential applications
• Deep black, full square mono cells with black frame



Easy handling and optimum utilization of roof space
• Smaller module format
• Low weight - just 12kg/m²




Excellent low light performance on cloudy days, mornings and evenings
• Mono cell technology
• Anti-reflective coating



Highly reliable due to stringent quality control
• PID resistant

LINEAR PERFORMANCE WARRANTY


10 Year Product Warranty • 25 Year Linear Power Warranty




THE **Quadmax** MODULE TSM-DC80.08

DIMENSIONS OF PV MODULE


unit:mm



Back View



I-V CURVES OF PV MODULE(210W)



ELECTRICAL DATA (STC)

Peak Power Watts- P_{MAX} (Wp)	210	215
Power Output Tolerance- P_{MAX} (%)	0 ~ +3	
Maximum Power Voltage- V_{MPP} (V)	37.6	38.4
Maximum Power Current- I_{MPP} (A)	5.59	5.60
Open Circuit Voltage- V_{OC} (V)	46.7	46.7
Short Circuit Current- I_{SC} (A)	5.90	5.96
Module Efficiency η_m (%)	16.4	16.8

STC: Irradiance 1000 W/m², Cell Temperature 25°C, Air Mass AM1.5 according to EN 60904-3.
Typical efficiency reduction of 4.5% at 200 W/m² according to EN 60904-1.

ELECTRICAL DATA (NOCT)

Maximum Power- P_{MAX} (Wp)	156	160
Maximum Power Voltage- V_{MPP} (V)	34.8	35.2
Maximum Power Current- I_{MPP} (A)	4.49	4.55
Open Circuit Voltage- V_{OC} (V)	43.3	43.3
Short Circuit Current- I_{SC} (A)	4.77	4.81

NOCT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1 m/s.

MECHANICAL DATA

Solar cells	Monocrystalline 125 × 125 mm (5 inches)
Cell orientation	72 cells (6 × 12)
Module dimensions	1581 × 809 × 35 mm
Weight	14.9 kg
Glass	3.2 mm, High Transmission, AR Coated Tempered Glass
Backsheet	White
Frame	Black Anodized Aluminium Alloy
J-Box	IP 65 or IP 67 rated
Cables	Photovoltaic Technology cable 4.0 mm ² , 900 mm
Connector	MC4 or MC4 Compatible

TEMPERATURE RATINGS

Nominal Operating Cell Temperature (NOCT)	44°C (±2°C)
Temperature Coefficient of P_{MAX}	-0.40%/°C
Temperature Coefficient of V_{OC}	-0.31%/°C
Temperature Coefficient of I_{SC}	0.05%/°C

MAXIMUM RATINGS

Operational Temperature	-40~+85°C
Maximum System Voltage	1000V DC (IEC)
Max Series Fuse Rating	10A

WARRANTY

10 year Product Workmanship Warranty

25 year Linear Power Warranty

(Please refer to product warranty for details)

PACKAGING CONFIGURATION

Modules per box:	30 pieces (Standard Box) 38 pieces (Small Box)
Modules per 40' container:	840 pieces (Standard Box) 532 pieces (Small Box)

CERTIFICATION

