

THE TALLMAX^M

FRAMED 144 LAYOUT MODULE



144 LAYOUT
MONOCRYSTALLINE MODULE

395-420 W
POWER OUTPUT RANGE

20.9%
MAXIMUM EFFICIENCY

0~+5W
POWER SELECTION

PRODUCTS

TSM-DD15M(II)

POWER RANGE

395-420W



High power Mono Perc

- Up to 420W front power and 20.9% module efficiency with half-cut and MBB (Multi Busbar) technology bringing more BOS savings
- Lower resistance of half-cut and good reflection effect of MBB ensure high power



High reliability

- Mechanical performance: Up to 5400 Pa positive load and 2400 Pa negative load and fire class rating C



High energy generation

- Excellent IAM and low light performance validated by 3rd party with cell process and module material optimization
- Lower temp coefficient (-0.34%) and NOCT bring more energy leading to lower LCOE
- Better anti-shading performance and lower operating temperature

Founded in 1997, Trina Solar is the world's leading total solution provider for solar energy. With local presence around the globe, Trina Solar is able to provide exceptional service to each customer in each market and deliver our innovative, reliable products with the backing of Trina as a strong, bankable brand. Trina Solar now distributes its PV products to over 100 countries all over the world. We are committed to building strategic, mutually beneficial collaborations with installers, developers, distributors and other partners in driving smart energy together.


Comprehensive Products and System Certificates

IEC61215/IEC61730/IEC61701/IEC62716/UL1703
 ISO 9001: Quality Management System
 ISO 14001: Environmental Management System
 ISO14064: Greenhouse Gases Emissions Verification
 ISO45001: Occupation Health and Safety Management System






PERFORMANCE WARRANTY

12 Year Product Warranty · 25 Year Power Warranty




From the 2nd year to the 25th year, the average annual power decline will be no more than 0.6%.


DIMENSIONS OF PV MODULE(mm)



I-V CURVES OF PV MODULE(405W)



P-V CURVES OF PV MODULE(405W)



ELECTRICAL DATA (STC)

Peak Power Watts- P_{MAX} (Wp)*	395	400	405	410	415	420
Power Selection P_{MAX} (W)	0 ~ +5					
Maximum Power Voltage- V_{MPP} (V)	40.1	40.3	40.5	40.7	40.9	41.0
Maximum Power Current- I_{MPP} (A)	9.86	9.92	10.00	10.07	10.15	10.25
Open Circuit Voltage- V_{OC} (V)	48.7	49.0	49.2	49.4	49.6	49.7
Short Circuit Current- I_{SC} (A)	10.37	10.45	10.52	10.59	10.66	10.76
Module Efficiency η_m (%)	19.7	19.9	20.2	20.4	20.7	20.9

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5.

*Measuring tolerance: ±3%.

ELECTRICAL DATA (NOCT)

Maximum Power- P_{MAX} (Wp)	298	301	305	309	313	317
Maximum Power Voltage- V_{MPP} (V)	37.7	38.0	38.1	38.4	38.6	38.8
Maximum Power Current- I_{MPP} (A)	7.90	7.93	8.01	8.05	8.11	8.18
Open Circuit Voltage- V_{OC} (V)	45.9	46.1	46.3	46.5	46.6	46.7
Short Circuit Current- I_{SC} (A)	8.36	8.42	8.48	8.54	8.59	8.66

NOCT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

MECHANICAL DATA

Solar Cells	Monocrystalline
Cell Orientation	144 cells (6 × 24)
Module Dimensions	2015 × 996 × 35 mm (79.33×39.21×1.38 inches)
Weight	22.0 kg (48.5 lb)
Glass	3.2 mm (0.13 inches), High Transmission, AR Coated Heat Strengthened Glass
Encapsulant Material	EVA
Backsheet	White
Frame	35 mm (1.38 inches) Anodized Aluminium Alloy
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm ² (0.006 inches ²), Portrait: N 280mm/P 280mm(11.02/11.02inches) Landscape: N 1400 mm / P 1400 mm (55.12/55.12 inches)
Connector	PV-KBT4(female),PV-KST4(male) / TS4

TEMPERATURE RATINGS

NOCT (Nominal Operating Cell Temperature)	43 C (±2 C)
Temperature Coefficient of P_{MAX}	-0.34%/ C
Temperature Coefficient of V_{OC}	-0.25%/ C
Temperature Coefficient of I_{SC}	0.04%/ C

(Do not connect Fuse in Combiner Box with two or more strings in parallel connection)

MAXIMUM RATINGS

Operational Temperature	-40~+85 C
Maximum System Voltage	1000V DC (IEC) 1000V DC (UL)
Max Series Fuse Rating*	20A / 25A

* 20A Default / 25A upon special request

WARRANTY

12 year Product Workmanship Warranty
25 year Power Warranty

(Please refer to product warranty for details)

PACKAGING CONFIGURATION

Modules per box: 30 pieces
Modules per 40' container: 660 pieces